

#### Intended use

Mipa 2K-HS-Express-Klarlack CX 4 is a high-quality acrylic clearcoat for a fast and efficient refinish (express technology), which ensures extremely fast drying by oven as well as by air. This special drying property offers saving potentials in terms of spray booth occupancy, stoving times as well as working time. This leads to a considerable reduction in operating costs and increases the throughput. Another major advantage is that Mipa 2K-HS-Express-Klarlack CX 4 can be polished quickly when it has been mixed with Mipa 2K-HS-Express-Härter HX 4:

After the drying of 10 minutes at 60 °C or 20 minutes at 40 °C, the painted parts can be polished immediately after the cooling. Alternatively it can be polished after a drying time of 1 hour at room temperature.

In combination with Mipa 2K-HS-Härter HS 10, the clearcoat can be polished as follows:

After the drying of 10 minutes at 60 °C or 15 minutes at 40 °C, the painted parts can be polished immediately after the cooling. Alternatively it can be polished after a drying time of 70 - 80 minutes at room temperature.

Mipa 2K-HS-Express Klarlack CX 4 is suitable for spot repair and partial paintwork and also for complete paintwork when mixed with hardener Mipa 2K-HS-Härter HS 25. In combination with hardener Mipa 2K-HS-Härter HS 25 the drying is as follows:

After the drying of 15 minutes at 60 °C or 30 minutes at 40 °C, the painted parts can be polished immediately after the cooling. Alternatively it can be polished after a drying time of 3 - 4 hours at room temperature.

Ready for use after adding the hardener. Perfectly resistant to weathering and environmental conditions, resistant to yellowing and durable gloss retention.

Spreading rate: 9,0 - 10,0 m<sup>2</sup>/l

#### Processing instructions

	Colour colourless		
	Mixing ratio Hardener	by weight (lacquer : hardener)	by volume (lacquer : hardener)
	Mipa 2K-HS-Express-Härter HX 4		2 : 1
	Mipa 2K-HS-Härter HS		2 : 1
	Mipa 2K-HS-Härter HS 25	-	2 : 1
	Hardener		
W	for complete paintwork	for partial pain	twork
	Mipa 2K-HS-Härter HS 25	Mipa 2K-HS-Exp	ress-Härter HX 4
		Mipa 2K-HS-Här	ter HS 10
$\square$	Pot life		

approx. 45 min with Mipa 2K-HS-Express-Härter HX 4 at 20 °C approx. 45 min with Mipa 2K-HS-Härter HS 10 at 20 °C approx. 60 min with Mipa 2K-HS-Härter HS 25 at 20 °C



Thinner

Version: en 0120 This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com

# Mipa 2K-HS-Express-Klarlack CX 4

Technical data sheet



Г	-	-	
	L		s
	5	2	0

## Spray viscosity

Ready for use after adding the hardener

gravity spray gun	
17 - 20 s 4 mm DIN	

1	Application mode					
	Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
	gravity spray gun (high pressure)		2 - 2,5	1,2 - 1,3	1,5 - 2	-
	HVLP (low pressure)	-	2 - 2,2	1,2 - 1,3	1,5 - 2	
	HVLP/ internal nozzle pressure	-	0,7	-	1,5 - 2	-

Airmix/Airless



## Flash-off time

3 - 5 min between coats

5 - 10 min prior to oven drying



### Dry coat thickness

40 - 60 µm



Drying time object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
20 °C HX 4/ HS 10	15 - 20 min	35 - 45 min	2 h		
20 °C HS 25	25 - 35 min	2 h	4 h		
60 °C HX 4/ HS 10		10 min	after cooling		
60 °C HS 25		15 min	after cooling		

Note	
Storage:	at least 3 years in unopened original container
VOC Regulation :	EU limit value for this product (category B/d): 420 g/l This product contains max. 420 g/l of VOC.
Processing conditions:	From +10 °C and up to 80 % relative air humidity. Ensure an adequate supply and exhaust air ventilation.

\_\_\_\_\_ Version: en 0120

This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com



Processing instructions:	Infrared drying (with Mipa 2K-HS-Express-Härter HX 4): infrared drying shortwave approx. 8 min infrared drying mediumwave approx. 10 - 15 min
	To ensure an optimal intermediate adhesion on basecoats, the clearcoat must be applied within 2 hours drying at room temperature. If this time is exceeded, it is necessary to add a hardener to the basecoat. The quantities to be added are:
	Mipa BC + 10 % (10:1) Mipa 2K-MS-Härter MS 10 or 2K-HS-Härter HS 10
	Mipa WBC + 5 % (20:1) Mipa WBC-Härter

Version: en 0120
This technical data sheet is supplied for informational purposes only! According to our information, all data and recommendations correspond to the state of art and are based on
years of experience in manufacturing our products. They do not exempt the user from his obligation to verify professionally, on his own responsibility, the suitability of our
products to the intended purpose under prevailing conditions. Safety data sheets and warnings on packaging must be observed. We reserve the right to modify and to complete
the information content at any time, without prior notice or obligation to update.

MIPA SE · Am Oberen Moos 1 · D-84051 Essenbach · Tel.: +49(0)8703/922-0 · Fax: +49(0)8703/922-100 · mipa@mipa-paints.com · www.mipa-paints.com